

## Product Description

The Beava Tile Trim by STS Ltd is made of high quality aluminium, this tile trim offers an attractive, professional finish to tile edging.

## Protection

In order to protect the trim in transport and whilst fitting and grouting the profiles have a transparent protective film to be removed after installation.



## Product Information

<b>What is it?</b>	<i>Anodized aluminum tile trim</i>
<b>When should it be used?</b>	<i>Edging trim for the perfect finish to tiling (corners &amp; edging)</i>
<b>Usage</b>	Suitable for all internal areas including Kitchens, bathrooms, wet rooms and living areas
<b>Drying time</b>	N/A
<b>Trim Length</b>	Each trim is 2.5m in length
<b>Matching with tile thickness</b>	Trim height is to be the next one up from the tile thickness. i.e. with a 8 or 9mm thick tile you would use a 10mm trim.

## Installation

1. Trowel tile adhesive over the area that forms the perimeter of the tiled covering.
2. Press the perforated anchoring leg of the trim into the tile adhesive and align, mechanical fix if required.
3. Trowel additional adhesive over the perforated anchoring leg to ensure full coverage.
4. Solidly embed the tiles so that the tiled surface is flush with the top of the profile, the profile should not be higher than the tiled surface, but rather up to approximately 1 mm lower.
5. Fill the joint completely with grout.

Aluminium AA 6063 T6 / UNS A96063 anodised to DIN 17611	
Si%	0.2-0.6
Fe%	0.35
Cu%	0.1
Mn%	0.1
Mg%	0.45 - 0.9
Zn%	0.1
Ti%	0.1
Cr%	0.1
Al	Balance

